


Datasheet

Hörmann Tree

Part No: 100592



About the product

Hörmann Tree is a wired interface for the seamless integration of Hörmann garage door openers into the LOXONE system. Using LOXONE Tree and the Hörmann Communication Protocol (HCP), it enables reliable, bidirectional communication and real-time control.

Features:

- HCP1 and HCP2 are supported
- Automatic drive detection
- Bidirectional communication
- Status monitoring (status, cycles, operating hours)
- Easy setup via Plug & Play
- Full operation and control in the LOXONE App

Technical Data

Power Supply	10 ... 28VDC
Power consumption	typ. 0.06 W, max. 0.07 W

Interfaces

Wi-Fi	Connection to local Network Wi-Fi 2.4 GHz: 802.11 b/g/n/ax 2 400 ... 2 483.5 MHz (max. 100 mW EIRP) Wi-Fi 5 GHz: 802.11 n/ac/ax 5 150 ... 5 350 MHz (max. 200 mW EIRP) 5 470 ... 5 725 MHz (max. 200 mW EIRP) This device is restricted to indoor use only when operating in the 5 150 to 5 350 MHz frequency range in: AT, BE, BG, CY, CZ, DE, DK, EE, EL, ES, FI, FR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, LI, NO, CH. The device is also restricted to indoor use in the United Kingdom.
Hörmann HCP Interface	Compatible with Hörmann Communication Protocol 1 and 2 (HCP) The device recognizes automatically which garage door operator is connected and which HCP version is used.

Ambient Conditions

Temperature	-20 ... 65°C / -4 ... 149°F
Humidity	max. 95% r.H. (non condensing)

Compatible Hörmann operators

Compatible Hörmann operators	An up-to-date List of compatible Hörmann operators is available online: shop.loxone.com/product/100592-hoermann-tree/
------------------------------	---

Connection Terminals


Wire cross-section	0.28 ... 0.8 mm ² / AWG 23 ... 18
Stripping length	5 ... 6 mm / 0.2 ... 0.24"
Temperature resistance	-40 ... 105 °C / -40 ... 221 °F

Connecting Cable

Wire cross-section	0.2 mm ² / AWG 24
Temperature resistance	80 °C / 176 °F
Length	100 mm / 3.94"
Connector	Modular 6P6C (RJ-12)
Part. No.	000588

Connection Diagram

Connection Diagram



Product Characteristics

Colours	Green: RAL 6018
Finish	Matte

Weight & Dimensions

Net weight	15 g
Total weight	35 g
Product dimensions	38.3 x 34.3 x 10.5 mm / 1.50 x 1.35 x 0.41" (L x W x H)
Product dimensions drawing	
Pack size	79 x 79 x 41 mm / 3.11 x 3.11 x 1.61" (L x W x H)

Certifications & Standards

Safety class	IP20
--------------	------

Certifications	
----------------	---



Installation must be carried out by a qualified electrician in accordance with the relevant regulations.

Published by


Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com

Loxone UK Ltd.
The Forum
Station Road
Theale, RG7 4RA
United Kingdom

Datenblatt

Hörmann Tree

Part No: 100592



Über das Produkt

Hörmann Tree ist eine kabelgebundene Schnittstelle zur nahtlosen Integration von Hörmann Garagentorantrieben in das LOXONE System. Über LOXONE Tree und das Hörmann Communication Protocol (HCP) ermöglicht es eine zuverlässige, bidirektionale Kommunikation und Steuerung in Echtzeit.

Features:

- HCP1 und HCP2 werden unterstützt
- Automatische Antriebserkennung
- Bidirektionale Kommunikation
- Statusüberwachung (Zustand, Zyklen, Betriebsstunden)
- Einfache Inbetriebnahme per Plug & Play
- Vollständige Bedienung und Steuerung in der LOXONE App

Technische Daten

Spannungsversorgung	10 ... 28VDC
Leistungsaufnahme	typ. 0.06 W, max. 0.07 W

Schnittstellen

WLAN	Verbindung zum lokalen Netzwerk WLAN 2,4 GHz: 802.11 b/g/n/ax 2 400 ... 2 483,5 MHz (max. 100 mW EIRP) WLAN 5 GHz: 802.11 n/ac/ax 5 150 ... 5 350 MHz (max. 200 mW EIRP) 5 470 ... 5 725 MHz (max. 200 mW EIRP) Hinweis zur Nutzung: Dieses Gerät darf im Frequenzbereich 5 150 bis 5 350 MHz in folgenden Ländern ausschließlich in Innenräumen betrieben werden: AT, BE, BG, CY, CZ, DE, DK, EE, EL, ES, FI, FR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, IS, LI, NO, CH. Auch im Vereinigten Königreich ist das Gerät nur für den Einsatz in Innenräumen vorgesehen.
Hörmann HCP Schnittstelle	Kompatibel mit Hörmann Kommunikationsprotokoll 1 und 2 (HCP) Das Gerät erkennt automatisch, welcher Torantrieb angeschlossen ist und welche HCP Version verwendet wird.

Umgebungsbedingungen

Temperatur	-20 ... 65°C / -4 ... 149°F
Luftfeuchtigkeit	max. 95% r.H. (nicht kondensierend)

Kompatible Hörmann Antriebe

Kompatible Hörmann Antriebe	Eine aktuelle Liste kompatibler Hörmann-Antriebe finden Sie online unter: shop.loxone.com/product/100592-hoermann-tree/
-----------------------------	---

Anschlussklemmen


Leiterquerschnitt	0,28 ... 0,8 mm ² / AWG 23 ... 18
Abisolierlänge	5 ... 6 mm / 0,2 ... 0,24"
Temperaturbeständigkeit	-40 ... 105 °C / -40 ... 221 °F

Verbindungskabel

Leiterquerschnitt	0.2 mm ² / AWG 24
Temperaturbeständigkeit	80 °C / 176 °F
Länge	100 mm / 3,94"
Konnektor	Modular 6P6C (RJ-12)
Art. Nr.	000588

Anschlussplan

Anschlussplan



Produkteigenschaften

Farbe	Grün: RAL 6018
Glanzgrad	Matt

Gewicht & Abmessungen

Nettogewicht	15 g
Bruttogewicht	35 g
Produktmaße	38,3 x 34,3 x 10,5 mm / 1,50 x 1,35 x 0,41" (L x B x H)
Produktmaßzeichnung	The technical drawing shows the terminal block from three perspectives: a top view, a side view, and a front view. The top view shows a rectangular block with dimensions 34,3 mm (width) and 38,3 mm (height). It features two sets of terminals labeled '24V GND' and 'G W'. The side view shows a height of 10,5 mm. The front view shows a rectangular block with a height of 10,5 mm.
Packmaß	79 x 79 x 41 mm / 3,11 x 3,11 x 1,61" (L x B x H)

Zertifizierungen & Standards

Schutzklasse	IP20
--------------	------

Zertifizierungen	
------------------	---



Die Installation muss von einer qualifizierten Elektrofachkraft gemäß den einschlägigen Vorschriften durchgeführt werden.

Veröffentlicht von

Loxone Electronics GmbH
Smart Home 1
4154 Kollerschlag
Austria
Tel: +43 7287 7070-0
loxone.com

Loxone UK Ltd.
The Forum
Station Road
Theale, RG7 4RA
United Kingdom